

Product Code:

7919

LEGEND EXTRA

Fully synthetic engine oil

Meets the requirements:

SAE 0W-30, ACEA C2/C3, API SN,
FORD WSS-M2C950-A, JAGUAR STJLR.03.5007,
LAND ROVER STJLR.03.5007, MB 229.51/229.52

Innovative bisynthetic (PAO+esters) motor oil for modern diesel- and petrol-powered engines. Ester oil components ensure excellent antiwear and antifriction properties due to the exceptional durability of the oil film, which, when combined with the excellent pumping quality, significantly extend the service life of the engine even in "Start-stop" driving modes. It has excellent starting characteristics and reduces fuel consumption. It efficiently fights against all types of deposits and maintains engine and turbo-compressor parts clean during the entire period between the replacements. It is used in engines with an enhanced oil replacement age (Long Life up to 30,000 km).

It is compatible with all neutralisation systems of waste gas, DPF, TWC, EGR and SCR due to the employment of the Mid SAPS technology. It is designed for diesel- and petrol-powered engines of MERCEDES-BENZ, FORD, JAGUAR and LAND ROVER passenger cars.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	62,64
Viscosity at 100°C	D 445	CSt	11,25
Viscosity at -35°C	D 5293	CP	6150
Viscosity index	D 2270		175
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	gKOG/kg	8,08

Volume:

1L	MN7919-1	60L	MN7919-60
5L	MN7919-5	208L	MN7919-DR
10L	MN7919-10	1000L	MN7919-IBC
20L	MN7919-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®