

Product Code:

7832

POWERBIKE 4-TAKT

Ester blend 4-stroke engine oil

Meets the requirements:

SAE 15W-50, API SM, JASO MA/MA2,
DUCATI, HONDA, KAWASAKI, SUZUKI, YAMAHA

Modern four-stroke engine oil with ester components for motorbikes, pit bikes, enduro and trial bikes. Provides optimum cold starts, maximum resistance at high temperatures and maximum shear stability. Usable in bikes with injection engines and catalytic converters, quads (ATVs), scooters etc.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	152,78
Viscosity at 100°C	D 445	CSt	17,16
Viscosity at -20°C	D 5293	CP	6605
Viscosity index	D 2270		122
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-34
TBN	D 2896	gKOG/kg	6,28

Volume:

1L met.	MN7832-1ME	60L	MN7832-60
10L	MN7832-10	208L	MN7832-DR
20L	MN7832-20	1000L	MN7832-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®