

Product Code:

7404

SAFARI

Universal engine oil

Meets the requirements:

SAE 20W-50
API SN/CH-4

MANNOL Safari is a multigrade engine oil with highly purified mineral basis for highly accelerated gasoline and diesel engines with and without turbocharge used in tough usage conditions. Contains low-ash additives to prolong the endurance of the catalyst. Has stable viscosity during the whole used period. Guarantees safe engine combustion at extreme loads.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	169,79
Viscosity at 100°C	D 445	CSt	17,78
Viscosity at -15°C	D 5293	CP	8537
Viscosity index	D 2270		115
Flash point COC	D 92	°C	232
Pour point	D 97	°C	-33
TBN	D 2896	gKOG/kg	6,74

Volume:

1L	MN7404-1	10L	MN7404-10
3L	MN7404-3	20L	MN7404-20
4L	MN7404-4	60L	MN7404-60
5L	MN7404-5	208L	MN7404-DR
7L	MN7404-7	1000L	MN7404-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®