

Product Code:

# 7904

# DIESEL TURBO

Synthetic engine oil

Meets the requirements:

SAE 5W-40  
ACEA A3/B4  
API CJ-4/SL  
VW-Norm 502 00/505 00

MANNOL Diesel Turbo is a modern engine oil of the latest generation. Suitable for modern, high output turbo diesel engines of cars, using direct fuel injection or "common rail" technology. Provides high pump ability at cold cranking. Has optimal viscosity at wide-ranging temperatures. Effectively prevents wear-out. Provides extreme cleanness of the engine components. Can be used in gasoline engines.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	850
Viscosity at 40°C	D 445	CSt	81,60
Viscosity at 100°C	D 445	CSt	13,39
Viscosity at -30°C	D 5293	CP	5864
Viscosity index	D 2270		167
Flash point COC	D 92	°C	236
Pour point	D 97	°C	-40
TBN	D 2896	gKOG/kg	10,67

Volume:

1L	MN7904-1	60L	MN7904-60
5L	MN7904-5	208L	MN7904-DR
10L	MN7904-10	1000L	MN7904-IBC
20L	MN7904-20		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®