

Product Code:

# 7505

# MOLIBDEN BENZIN

Semi-synthetic engine oil

Meets the requirements:

SAE 10W-40  
API SL/CF  
ACEA A3/B3

MANNOL Molibden Benzin 10W-40 is a multipurpose multigrade semi-synthetic engine oil for all modern engine types. Effectively reduces the wear-out on all the stages of the engine burn due to the formation of a unique protective film which endures extreme loads. Prevents formation of steel particles. Has optimal low-temperature characteristics and stable viscosity during the whole used period. Prevents oil "waste".

Product Characteristics:

Test	Method	Unit	Result
SAE-class			10W-40
Density at 15 °C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40 °C	D 445	CSt	97,50
Viscosity at 100 °C	D 445	CSt	13,90
Viscosity at -25 °C	D 5293	CP	6980
Viscosity index	D 2270		145
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
TBN	D 2896	gKOH/kg	8,06

Volume:

1L	MN7505-1	60L	MN7505-60
4L	MN7505-4	208L	MN7505-DR
10L	MN7505-10	1000L	MN7505-IBC
20L	MN7505-20		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®