

Product Code:

7906

ENERGY ULTRA JP

Synthetic engine oil

Meets the requirements:

SAE 5W-20, API SN, ILSAC GF-5, GM dexos1, FORD WSS-M2C945-A/B/WSS-M2C930-A/WSS-M2C925-A, CHRYSLER, HONDA, ACURA, MAZDA, MITSUBISHI, TOYOTA, NISSAN, SUBARU, ISUZU, SUZUKI, HYUNDAI, KIA

MANNOL Energy Ultra JP is a modern premium class engine oil for lubrication of all 4-stroke engines of Japanese, Korean and American light vehicles, minivans and SUV's. Ideal for up-to date gasoline engines with turbocharging and multi-valve technology (VTEC, VVT-i, CVT, VTC, VVL, VVTL-i, MIVEC etc.). The combination of unconventional base oils together with the latest additive technology guarantees a motor oil that provides exceptional protection against wear and keeps the engine clean while ensuring fast oil penetration of engine.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	830
Viscosity at 40°C	D 445	CSt	41,96
Viscosity at 100°C	D 445	CSt	7,87
Viscosity at -30°C	D 5293	CP	6181
Viscosity index	D 2270		162
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	gKOG/kg	8,05

Volume:

1L	MN7906-1	20L	MN7906-20
4L	MN7906-4	60L	MN7906-60
5L	MN7906-5	208L	MN7906-DR
7L	MN7906-7	1000L	MN7906-IBC
10L	MN7906-10		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®