

Product Code:

# 8207

# DEXRON VI

## Automatic transmission fluid

Meets the requirements:

GM Dexron® VI, FORD Mercon® LV, JASO 1A,  
TOYOTA ATF WS Lifetime, ALLISON C4,  
CHRYSLER ATF +4, HYUNDAI ATF SP-IV,  
KIA ATF-SP-IV, LEXUS ATF WS Lifetime,  
NISSAN Matic S, MB 236.14, SHELL M-1375.4

MANNOL Dexron VI is a supreme performance automatic transmission fluid specially developed for General Motors vehicles. This fluid is formulated with exceptional quality base fluids and advanced additive technology to provide outstanding oxidation resistance, friction durability, wear protection and shear stability. Enhanced foam control maintains responsive shifts and reduces wear on bearings, bushings and gears. Special rust and corrosion inhibitors protect critical parts against rust and corrosion throughout the service life.

### Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	850
Viscosity at 40°C	D 445	CSt	27,55
Viscosity at 100°C	D 445	CSt	5,74
Viscosity index	D 2270		157
Flash point COC	D 92	°C	214
Pour point	D 97	°C	-52
Brookfield dynamic viscosity at -40°C	D 2983		9 960

### Volume:

1L	MN8207-1	60L	MN8207-60
4L	MN8207-4	208L	MN8207-DR
10L	MN8207-10	1000L	MN8207-IBC
20L	MN8207-20		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®