

Product Code:

7914

ENERGY FORMULA JP

Synthetic engine oil

Meets the requirements:

SAE 5W-30, API SN, ILSAC GF-5, GM dexos1,
ACURA, HONDA, HYUNDAI, INFINITI, KIA, LEXUS,
MITSUBISHI, NISSAN, SUBARU, SUZUKI, TOYOTA

MANNOL Energy Formula JP is modern premium class engine oil for the lubrication of all four-stroke engines of Japanese, Korean and American light vehicles, minivans and SUVs. Optimum for up-to-date diesel and petrol engines (GDI, D-4D and NEO-DI) with multi-valve technology and turbocharger (DOHC, VVT-i, VTC, CVVT, VTEC, VVL, VVTL-i, MIVEC etc.). The combination of unconventional base oils together with the latest additive technology guarantees an engine oil that provides exceptional protection against wear and keeps the engine clean while ensuring fast oil penetration of the engine.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	67,73
Viscosity at 100°C	D 445	CSt	11,50
Viscosity at -30°C	D 5293	CP	5872
Viscosity index	D 2270		165
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	gKOG/kg	10,40

Volume:

1L	MN7914-1	20L	MN7914-20
4L	MN7914-4	60L	MN7914-60
7L	MN7914-7	208L	MN7914-DR
10L	MN7914-10	1000L	MN7914-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®